


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification:	G06F 9/00, 13/14	AI	(11) International Publication Number:	WO 94/14114
			(43) International Publication Date:	23 June 1994 (23.06.94)
(21) International Application Number:	PCT/US93/11506		(81) Designated States:	AU, FL, HU, JP, KR, NO, NZ, PL, RU,
(22) International Filing Date:	29 November 1993 (29.11.93)			European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(30) Priority Data:	987,365	7 December 1992 (07.12.92)	US	Published
				With international search report.
(71) Applicant:	OVERLORD, INC. [US/US]; 90 South LaSalle Street, Suite 2760, Chicago, IL 60603 (US).			
(72) Inventor:	KENNEDY, Donald, J.; 1725 Westbridge Court, Southbridge Commons, Schaumburg, IL 60194 (US).			
(74) Agents:	VARGO, Paul, M. et al.; Dressler, Goldsmith, Shore & Milnamow, Two Prudential Plaza, Suite 4700, Chicago, IL 60601 (US).			

(54) Title: INTERCEPTION SYSTEM AND METHOD INCLUDING USER INTERFACE



(57) Abstract

A method of intercepting pre-existing computer instructions in order to modify and/or enhance pre-existing program units (30) and supply user entry points determines, in one or more embodiments, if a reference can be found in a program unit (30). If so located, the corresponding method provides user code entry points (steps 72, 78) before and after the intercepted instruction, perhaps in modified and/or enhanced form, is executed (step 76). Blocks of user supplied code can be provided at the entry points to enhance, upgrade, and/or expand upon the intercepted instruction, thereby enhancing the pre-existing program unit (30).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MD	Republic of Moldova	TJ	Tajikistan
DE	Germany	MG	Madagascar	TT	Trinidad and Tobago
DK	Denmark	ML	Mali	UA	Ukraine
ES	Spain	MN	Mongolia	US	United States of America
FI	Finland			UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

INTERNATIONAL SEARCH REPORT

International application No
PCT/US93/11506

A. CLASSIFICATION OF SUBJECT MATTER

IPC(S) : G06F 9/00; 13/14

US CL : 395/375

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/375, 700

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS: search terms: service routine, request, call

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,109,515 (Laggis et al) 28 April 1992 See abstract. See column 2, lines 37-60, column 3, lines 4-29, column 5, lines 44-68, column 6, lines 14-36, column 7, lines 11-35, and figures 3 and 4.	1-9
Y,P	US, A, 5,241,634 (Suzuki) 31 August 1993 See abstract, column 3, lines 37-68, column 4, lines 1-6 and 11-47.	1-9
X	US, A, 4,768,150 (Chang et al) 30 August 1988 See abstract, column 2, lines 65-68, and column 3, lines 1-53.	1-9
Y		



Further documents are listed in the continuation of Box C



See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be part of particular relevance
- *E* earlier document published on or after the international filing date
- *L* document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another claim or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date and not in conflict with the application but disclosing principle or theory underlying the invention

X

document of particular relevance; the claimed invention is considered novel or cannot be considered to involve step when the document is taken alone

Y

document of particular relevance; the claimed invention is considered to involve an inventive step when combined with one or more other such documents being obvious to a person skilled in the art

&

document member of the same patent family

or priority
claim(s) thecannot be
inventive stepcannot be
inventive
situation

Date of the actual completion of the international search

19 January 1994

Date of mailing of the international search report

MAR 03 1994

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D C 20231

Authorized officer

Parsh Lal

Facsimile No NOT APPLICABLE


Telephone No (703) 305-9715

INTERNATIONAL SEARCH REPORT

International application No
PCT/US93/11506

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X --- Y	US, A, 5,124,909 (Blakely et al) 23 June 1992 • See abstract, column 1, lines 25-68, and column 2, lines 1-13.	1-9



This Page Blank (uspto)




FIG. 1




FIG. 2

This Page Blank (uspto)




FIG. 3

This Page Blank (uspto)

INTERCEPTION SYSTEM AND METHOD
INCLUDING USER INTERFACE

Field of the Invention

5 The invention relates to single and multiprocessor computer systems that supply system services to requesting program units running on or in such systems. More particularly, the invention relates to methods of enhancing or modifying the run-time operation of selected, pre-existing program units.

10 Background of the Invention

Computer systems have, over a period of years, evolved from stand-alone individual processors to various forms of multi-processor systems. Many computer systems use program units, sometimes referred to simply as "programs".

15 The program units contain computer instructions which the computer system can execute in order to perform specific functions. These program units may have been created from other program units. However, in most cases, a human being was involved at some point in the creation of the set of computer instructions being executed.

20 Program units are intended to meet certain known or projected needs when implemented. However, most program units designed in the past or being designed in the present will not conform to all future needs.

25 Prior art systems have approached the need to be flexible to deal with future needs in many ways. In many cases, prior approaches have not been cost effective and/or do not allow the user many options on their implementation.

The evolution and combination of new hardware systems, new operating systems, new program units, new system procedures, new data structures, or new user interfaces may require that the original program units
5 be modified, recompiled, or worse, abandoned due to compatibility and/or cost related problems. Some of the prior art approaches require extensive training on both the use and implementation of these methods. Some users may not be able to afford the time, money, and human
10 resources to implement the prior art approaches.

This need for flexibility in updating or modifying existing programs is especially apparent in multi-processor distributed systems. Several different types of problems have provided the impetus to the drive
15 toward multi-processor systems.

One impetus has been a desire to share information more effectively among diverse users. An approach to this problem has been to couple a variety of processors, which may or may not be the same, together
20 via a local area network. Such networks enable many different individuals and their associated processors to have access to common information and to have access to one another.

Yet another impetus toward multi-processor environments has been a desire to create highly reliable computer systems out of less reliable components. Such
25 systems are typically used in environments such as banking, transaction processing, or inventory control, wherein reliability is of paramount importance.

One such family of computer systems is marketed by Tandem of Cupertino, California. Tandem systems can be implemented in stand-alone, multiple processor configurations, or as multiple interconnected
30 nodes. Each node corresponds to one or more multiple processor systems.
35

Where major program systems, which might include dozens of program units, to support multiple remote transaction terminals or inventory control functions are installed and running on a production basis in a multiple processor environment, the above-noted problem of updating and maintaining program units becomes very difficult and expensive to solve. For example, a new operating system might be adopted by the hardware vendor. In such an instance, the system operator might have to install the new operating system to receive continuing support and operating system maintenance.

If the change in operating systems is not transparent to the existing program systems, they may need to be modified or recompiled. This process is not only expensive and time consuming, but in a multi-program, multi-processor environment can result in errors which could cause catastrophic results.

In addition, where the software had been obtained from a third party vendor, the user might not have the source code or documentation necessary to make modifications, expansions, or recompilations. Worse yet, the third party vendor will, in all likelihood, not continue to support or provide new releases to the user.

Thus, there continues to be a need to be able to safely upgrade or modify existing programs in a cost effective fashion as the requirements or the environment change. Preferably, this need could be met by system operating personnel without a need to return to the original software vendor or to modify the original provided program units.

In addition, in a multiple processor system, the operating environment is continuously changing. As a result, the mix of resources, available processors, and the like, available each time a program unit or a

process is initiated, will be different, depending on what other program units or processes are active at any given time.

Thus, there is continuous problem of resource allocation and management which must be addressed in such systems. One known approach, marketed by the assignee of the present application under the name of "Automatic Network Balancing System" for Tandem computers, provides resource allocation services and resource management in such environments based on predetermined and fixed allocation methods.

In the known automatic network balancing system, the performance factors which are taken into account to select the best or most appropriate processor to which a process is to be allocated, include availability or busy state of a given processor, available memory, swap rate, dispatch rate, memory queue length, jobs that are available on the ready list, as well a number of others. The various performance factors are evaluated using a weighing system. The processor which appears to be most appropriate is then selected to run the process.

The known load balancing system has been very successful and can be used to substantially increase performance of Tandem-like systems. Nevertheless, the method of selecting the most appropriate processor to be allocated to carry out a given task does not take into account site or user needs for diversity or customization between one installation and another.

Thus, there continues to be a need for a more flexible approach which can take into account variations from site to site. Preferably, such an approach could be implemented to allow site specific input to the processor selection process or to expand upon the services provided to a given process which is being

executed. Preferably, the implementation will be transparent to the respective process.

Summary of the Invention

5 This invention is directed to an apparatus and
a method of run-time interception of pre-existing
computer instructions in program units in order to
support user hooks or entry points which can be used to
10 modify and/or enhance the originating and/or receiving
program units, at the user's discretion. As a result,
the program units can meet the user's present needs and
allow modification by the users, on an as needed basis,
to support the future needs. Using the present
15 invention, this can be accomplished without requiring
the support and/or guidance and/or expertise of the
original authors and/or inventors of the program units,
being intercepted or any additional physical,
electronics, or mechanical device.

 The above result is achieved by intercepting
20 system service calls which are made by executing program
units at run time when the program units request that
the operating system of the computer system provide a
service on their behalf. The interception can take
place in the main program units, user library program
25 units, system library program units, or a combination of
the program units listed above.

 The method also contemplates that the
interception of the system service calls and user hooks
or entry points would be placed in several types of
30 program units. This gives the users many options as to
where the interceptions of the system service calls will
take place. Further, it allows the user to implement
the invention on a program unit by program unit basis,
if desired, or to implement the invention on a system by
35 system basis.

In accordance with one aspect of the invention, an apparatus and a method are provided for altering or translating one or more steps of a pre-existing method for carrying out a predetermined function. Site or user defined steps or functions can be incorporated into the process for customization or specialization.

The method can be used, for example, for allocating resources within a multiple processor computer system. In other aspects of the invention, different types of functions can be implemented beyond those specified in the pre-existing method.

The method includes detecting a step which is a candidate for alteration. The alteration process could include carrying out a different function from that which the step initially requested, or for translating or expanding upon the step.

A determination is made if a previously defined, user supplied, pre-alteration set of steps is to be executed before carrying out one or more predetermined altering or translating steps. In response to this determining step, the group of site or user supplied pre-alteration or pre-translation steps is executed as indicated.

The method then includes executing the one or more predefined altering or translating steps. Such steps could include, in accordance with one aspect of the invention, determining which of a plurality of available resources is to be used to carry out the requested step which is the candidate for alteration.

Alternately, the predefined altering steps could provide enhanced functions not called for in the original candidate steps. Such enhanced functions may have become desirable, so long as they can be provided

so as to be transparent to the original candidate-step or steps.

5 The method then makes a determination as to whether or not there are one or more post-alteration, site or user supplied steps. These steps can then be executed as indicated after executing the set of altering steps.

10 In accordance with yet another aspect of the invention, the method can be used for the purpose of allocating resources within a multiple node, multiple processor system. Each of the nodes can include one or more computer processors. The nodes can be physically displaced from one another, and can be coupled together via communication lines.

15 This aspect includes the steps of:
 carrying out a sequence of steps in a predetermined process;

 detecting a step in the sequence which is to be carried out and which is a candidate for translation;
20 intercepting the detected step and determining if a previously defined, user supplied, pre-translation set of steps exists;

 interrupting the sequence and executing the user supplied pre-translation set of steps as indicated;
25 translating the candidate step into a predetermined sequence of one or more predetermined translated steps;

 subsequent to the translation step, determining if a previously defined, user supplied,
30 post-translation set of steps exists;

 executing the user supplied, post-translation set of steps as indicated; and

 returning to the sequence of steps immediately after the detected step, thereby continuing the process.

In yet another aspect of the invention, the method can be used for the purpose of resource allocation for the purpose of not only optimizing processing throughput, but also for the purpose of
5 creating redundant databases automatically in spaced apart locations for purposes of other functions, such as disaster recovery, for instance.

These and other aspects and attributes of the present invention will be discussed subsequently with
10 reference to the following drawings and accompanying specification.

Brief Description Of The Drawing

Figure 1 is a schematic diagram of a multiple
15 node, multiple processor network;

Figure 2 is a schematic diagram of an environment in which a program unit might be executed;

Figure 3 is a flow diagram of a method in accordance with the present invention; and

20 Figure 4 is a flow diagram of an alternate method in accordance with the present invention.

Detailed Description of the Preferred Embodiment

While this invention is susceptible of
25 embodiment in many different forms, there is shown in the drawing, and will be described herein in detail, specific embodiments thereof with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and
30 is not intended to limit the invention to the specific embodiments illustrated.

The present method makes it possible for a program user or a system operator to update and modify pre-existing programs without requiring the recompiling
35 of the source codes of the respective program unit(s).

This is accomplished by intercepting selected calls or references to procedures, program units, or variables that can be external or internal to a pre-existing executing program unit. One type of interceptable
5 instruction is an operating system service call.

On interception, the operating system will look for the called procedure in a library linked to the executing program unit, if such exists. In the absence of a program related library, or in the absence of a
10 match with the called procedure in the executing program unit, the operating system will then attempt to find the called procedure or program unit in its system library.

Where a match is found in either the program library or the system library, that procedure or program unit is then executed. If there is no match, an
15 indication of a run-time error should be returned to the calling program unit.

The present method makes available "user hooks" in the respective library procedures or program units. The phrase "user hooks" as used herein refers to
20 intentionally created entry points or steps wherein a user or system operator can insert one or more computer instructions (blocks of code) for the purpose of transparently updating or modifying the executing
25 program unit. Hence, the user has greater control over its computer system(s) and is able to make modifications or enhancements outside of the executing program unit. This avoids any need to modify or recompile that program unit.

Another advantage of the present method is that it can be used where the program library is incorporated into the program unit itself. The user
30 hooks provide a way for a user or operator to create a bridge between various versions or releases of software packages, as well as program units.
35

Figure 1 illustrates schematically a multiple processor computer network 10. The network 10 includes a plurality of nodes 12 through 18.

Each of the nodes 12 through 18 can include one or more computer systems. Representative examples include Tandem-type multiple processor computer systems which might include up to 16 processor modules.

It will be understood that a node, such as node 12, could be implemented as a stand-alone, single processor computer system. Neither the number of processors, nor the architecture thereof, nor the presence or absence of communication links are a limitation of the present invention. The present invention can be advantageously practiced in conjunction with a single, stand-alone system.

Each of the nodes 12 through 18 can communicate with at least one other node via communication channels, such as the channels 20a through 20e. The network 10 can be geographically disbursed with the nodes 12 through 18 coupled, at least in part, via long distance communication links or other communications methods.

Figure 2 illustrates schematically a program unit 30 which is to be executed on a processor 32. As is conventional, the program unit 30 communicates with the processor 32 via an operating system 34. The operating system 34 provides a variety of services to the executing program unit.

The program unit 30 and operating system 34 would normally be stored in one or more storage devices or units of the processor 32. The details of such storage and the process wherein the operating system 34 initiates executing of the program unit 30 on the processor 32 are known and are not a limitation of the present invention.

As has long been recognized, one aspect of an operating system is to enhance the efficiency of utilization of the processor 32 as well as to improve the speed and ease of creation of programs such as the program unit 30. In this regard, the operating system 34 provides a variety of predefined commands, so-called "System Service Calls" (SSC), which carry out certain predefined functions when requested by a calling program unit.

Representative system service calls include a command to carry out a "read" function. A "read" request, based on supplied parameters, could request a read from a disk drive or other types of magnetic storage, or could request a read from a terminal or other devices.

Alternately, the operating system might support a system service call, such as a "write" to a storage unit or a device. A "write" request could send data or programs to communication lines, printers, or the like. A more extensive list of system service calls of a type supported by Tandem's GUARDIAN Operating System is attached hereto as Exhibit A.

In accordance with the present invention, there is interposed between the program unit 30 and the operating system 34 a functional layer 36 which includes the "user hooks" or entry points. At these points, an operator, a user, or a site can expand upon or modify external references or calls intercepted by the operating system.

Once an instruction has been intercepted, a first user hook is then checked or executed. This entry point can include an initial block of user or operator supplied code. This initial or "prior" block is to be executed before any modification and/or enhancement of

the function which is the subject of the intercepted instruction is carried out.

5 The intercepted call or service request may then be executed as required. This execution, as described below, can be modified and/or enhanced, or expanded upon in a predetermined fashion.

10 Then, a second user hook or entry point may be checked or executed to determine whether or not there is any post-translation, user, or site specific code which is to be executed. If so, that code is executed. Finally, appropriate parameters and/or data may be returned to the program unit 30 which had previously made the service request or call.

15 In accordance with the present invention, the interception process is carried out in one embodiment using a hierarchy that is very often imposed by the operating system between program library calls and system library calls. As a first step in carrying out the call or the functional request, if a program library 20 30a is associated with the program unit 30, the operating system 34 checks the program library 30a first to determine if the intercepted external reference or call is present in the program library.

25 By providing counterparts in the library 30a to some or all of the system service calls or functions of the operating system 34 before the operating system intercepts requests for such services from the program unit, the corresponding procedure in the program (not the system) library will be executed. This provides a 30 vehicle to modify or expand such requests in a predetermined fashion.

35 Hence, by associating with the program library structure 30a, a plurality of modified operating system calls, when the program 30 executes a particular service call, service can be provided in accordance with that

request. In addition, on a substantially transparent basis to the executing program unit, the service can be enhanced and/or modified, or completely changed in a predetermined fashion. If and when the appropriate
5 parameters and/or data are then returned to the program unit 30, that program can then continue executing subsequent instructions.

It will be understood that the library 30a is not required to practice the present method. An
10 equivalent structure can be implemented in the operating system 34 as discussed subsequently or in the program unit 30 itself.

Example 1 illustrates the process. Subsequently referred to line numbers are listed along
15 the left-hand margin of Example 1.

In Example 1, a read operation present in the program unit 30 could be intercepted and/or modified or translated on a substantially transparent basis in the interface layer 36. Line 40 of Example 1, defines the
20 procedure to be executed as a "read" function with n parameters associated therewith.

The read process begins in a line 42. Line 44 represents a first user hook or entry point. A call is made to a procedure which includes one or more
25 previously specified site specific or operator specific instructions which are not normally part of the "read" procedure. Subsequent to the execution of the procedure of line 44, the actual "read" procedure can be carried out as indicated schematically in line 46.

30 It should be noted that the actual read procedure which could be carried out could be a read procedure which is expanded and/or substantially different from the originally contemplated and specified read procedure in the calling program unit 30. Thus, a

- 14 -

bridging function can be provided, if necessary, between different program versions and/or releases.


```
40 .   PROC READ (1, 2 .... n)
42     BEGIN
44     CALL PRIOR (1, 2 .... n)
46     JUMP TO READ FUNCTION VIA O/S LOGICAL ADDRESS
5      48     CALL POST (1, 2 .... n)
50     END
      PROC PRIOR (1, 2 .... n)
10     BEGIN          USER INSTRUCTIONS CAN BE
                      INSERTED AT THIS POINT IF
                      DESIRED
      END
      PROC POST (1, 2 .... n)
15     BEGIN          USER INSTRUCTIONS CAN BE
                      INSERTED AT THIS POINT IF
                      DESIRED
      END
```

20

EXAMPLE 1

- 16 -

Line 48 is a second user hook or entry point. A procedure is called which includes one or more site specific or operator specific instructions which may be carried out after the read function is carried out. The
5 end of the procedure is indicated in line 50.

It will be understood that the location, number, or function of the user hooks are not a limitation of the present invention. In addition, the present invention contemplates the use of multi-levels
10 of entry points, such as in the program unit, the program library, or the system library.

Upon a return from the read procedure of Example 1 to the program unit 30, that program will continue execution which can be based on returned
15 parameters or data, if any, which resulted from the read procedure initiated therein. Hence, information actually supplied to the program unit 30 could come from a completely different location and/or source than that originally contemplated by the program unit 30 and this
20 change could be completely transparent thereto.

Figure 3 illustrates a flow diagram of an embodiment of the method of the present invention. The process of Figure 3 will be explained below in combination with the text of Example 1. In the
25 embodiment of Figure 3, the program library 30a has been previously linked to the program unit 30 and is available at run time. Using the above-noted hierarchal approach, the operating system 34 checks the library 30a first when the program unit 30 calls an external
30 function or service, or tries to initiate execution of an external procedure.

The library 30a has been previously loaded with procedures corresponding to at least some of the external references for the program 30. The names of
35 some of the previously loaded library procedures must be

the same as the names of system service calls that are to be expanded upon and/or modified. (Usually, this is regarded as an error to be carefully avoided!)

5 In addition, it is necessary to be able to acquire, usually via the operating system, the logical address(es) of the respective system service call(s) in the operating system's library to be intercepted. The respective library procedure requires this information to be able to call that service function without using
10 the name thereof.

For instance, in Example 1, a "read" system service call is to be intercepted and/or modified. The program library, as a result, includes a PROC READ. In line 46, to call the actual read in the operating system
15 library, a: JUMP TO LOGICAL ADDRESS OF SSC READ must be executed to prevent PROC READ from calling itself.

Referring to Figure 3, the execution of the program unit 30 has been previously initiated. Step 62 represents execution of the program unit 30 until an
20 external request of some sort is made or until the program unit 30 is completed, at which point it terminates in a step 64.

In the event that the program unit 30 makes an external request, such as a request for a "read" or
25 "write" for example, the operating system 34, in step 68, first checks the program library 30a, if any, to determine whether or not this function or procedure is found therein. If the called function, procedure, or external reference is located by the operating system 34
30 in the library 30a, for example, the "read" procedure of Example 1, that procedure is initiated.

In a step 72, the first user hook or entry point is encountered. This corresponds to the call at line 44 of Example 1. If there exists operator or site
35 specific procedures and/or code, such steps should be

executed. This corresponds to carrying out the procedure of line 44 of Example 1.

5 In a step 76, the system service call or other function, called by program unit 30, is carried out, corresponding to carrying out the "read" function of line 46 of Example 1. The executed procedure from the operating system that is executed may be different from that contemplated by the creator of the program unit 30.

10 In a step 78, the second or "post" user hook or entry point is encountered. This corresponds to carrying out the procedure of line 48 of Example 1. Then, there is a return to execution of the program unit 30 in a step 80. While executing user hook instructions, alternate return paths, such as step 80a or step 80b could be provided by the user.

15 In this example, if the called procedure or service request is not found in the library 30a, and if it is in the system library, then, in a step 70, the requested service or procedure is carried out, perhaps in combination with other services of the operating system-34. Any necessary parameters and/or data are returned to the program unit 30 which continues executing in step 62a.

20 As can be observed from the process of Figure 3, as a result of the site specific user supplied pre-translation and/or pre-modification steps, the first user hook, such as the process 44, along with the post-translation or post-modification steps, such as the process 48, it is relatively easy for an operator and/or a user to provide extensions, translations, and/or modifications to the original function being requested by the program unit 30. These are all outside of the program unit 30 and are substantially transparent to it.

25 Figure 4 illustrates an alternate embodiment of the present invention. In the embodiment of Figure 30
35

4, the program unit 30 need not have a library 30a associated therewith.

However, the names of the procedures or system service calls in the operating system library have been previously altered to distinguish them from the called procedure or "system service call" to be intercepted. With this change, the actual operating system call, under the new name, can subsequently be made. One of these procedures could correspond to the "open" procedure. Renaming pertinent system service routines in the system library, such as "open" to "sopen", as illustrated in Figure 4, step 34b, can be done when the operating system is compiled and linked together. In addition, corresponding procedures, as illustrated in Figure 4, step 72a, must be loaded into the system library with the original names of the system service calls to be intercepted.

If the respective system library procedures of the operating system had been previously modified and expanded upon as described above, it would be possible to carry out a corresponding user specified "prior" procedure as identified on line 44 of Example 1 in step 72a, analogous to the step 72 previously discussed. After executing corresponding and/or similar system service calls in step 76a, the user defined instructions represented by the "post" procedure of Example 1 can be executed in a plurality of steps 78a. Subsequently, the operating system 34 returns appropriate parameters and/or data, if any, to the program unit 30, which then continues executing in a step 62a.

Using the previously described method, either the embodiment of Figure 3 or that of Figure 4, makes it possible for a user and/or operator to upgrade, maintain, and/or modify program units, such as the unit 30, to deal with both a changing environment and also

changing functional requirements, now and in the future. It is also possible to modify and/or upgrade system service calls so as to provide substantially different and/or enhanced functions not previously available to the corresponding program units, such as the program unit 30, as well as operating system 34.

The above-described instruction interceptions are carried out at run-time, and are substantially transparent to the executing program unit. Source code for the program unit is not required to practice the present method.

By making the "user hooks" or entry points available, as described above, both before and after executing the corresponding system service calls, for example, users and/or operators will be able to more effectively manage, maintain, and upgrade their program units in a very cost effective fashion. Further, because the present method is substantially external to the respective program unit, there should be no impact to third party vendor or maintenance relationships.

- Additional representative examples of ways in which the methods of Figures 3 and/or 4 could be used include improved resource allocation in a multi-processor environment by including provision for user specific and/or operator specific modification to resource allocation routines. Redundant write operations can be provided when carrying out the write function to provide multiple, substantially transparent, sets of data which can be used for verification, disaster recovery functions or the like.

Thus, in accordance with the present invention a user interface is provided to, on a substantially transparent basis, modify requests made by an executing program unit for a variety of purposes. This modification process takes place substantially outside of the program unit. It can be substantially outside of the associated

operating system but can be readily modified by the operator and/or the user for purposes of customization.

5 The present invention has been discussed in terms of translating and/or modifying instructions at run time in a program unit, such as the exemplary program unit 30. It will be understood that the present methods can be used with any type of program unit, such as an application, a utility, or the like. Hence, the present method could also be used to translate and/or modify instructions in programs that may
10 be routinely thought of as part of the operating system.

It will also be understood that the embodiments of Figures 3 and/or 4 could be combined. In addition, it is also within the spirit and scope of the present invention to alternately merge some of the procedures of the program
15 library with the associated main program unit.

Example 2 is a further illustration of the method hereof in source code form.

From the foregoing, it will be observed that numerous variations and modifications may be effected
20 without departing from the spirit and scope of the invention. It is to be understood that no limitation with respect to the specific apparatus illustrated herein is intended or should be inferred. It is, of course, intended to cover by the appended claims all such modifications as
25 fall within the scope of the claims.

EXHIBIT A

5

PARTIAL LIST OF TANDEM'S GUARDIAN
OPERATING SYSTEM CALLS
(WITHOUT PARAMETERS)

ALTER

ALTER PRIORITY

10

APS DATA GETPARAM

CONTROL

CREATE

DEFINEADO

DEFINEINFO

15

MEASURINFO

NEWPROCESS

OPEN FILE

PRINTINFO

PRINTREAD

20

READ

WRITE


```
1. 000000 0 0 ? INSPECT, SYMBOLS, SAVEABEND
3. 000000 0 0
4. 000000 0 0
5. 000000 0 0
6. 000000 0 0
7. 000000 0 0
8. 000000 0 0
9. 000000 0 0
10. 000000 0 0
11. 000000 0 0
12. 000000 0 0
13. 000000 0 0
14. 000000 0 0
15. 000000 0 0
16. 000000 0 0
17. 000000 0 0
18. 000000 0 0
19. 000000 0 0
20. 000000 0 0
21. 000000 0 0
22. 000000 0 0
23. 000000 0 0
24. 000000 0 0
25. 000000 0 0
26. 000000 0 0
27. 000000 0 0
28. 000000 0 0
29. 000000 0 0
30. 000000 0 0
31. 000000 0 0
32. 000000 0 0
33. 000000 0 0
34. 000000 0 0
35. 000000 0 0
36. 000000 0 0
37. 000000 0 0
38. 000000 0 0
39. 000000 0 0
40. 000000 0 0
41. 000000 0 0
42. 000000 0 0
43. 000000 0 0
44. 000000 0 0

Copyright 1992, By Overlord Inc., All rights reserved
Author : Don Kennedy

Purpose : To demonstrate a method of intercepting pre-existing computer
instructions in order to modify and or enhance pre-existing
computer instructions and supply user hooks's, without the
requirement and or need of one or more of the following :

A. Viewing the original program unit(s) source code.
B. Viewing the original program unit(s) object code.
C. Re-compiling the original program unit(s) source code.
D. Prior knowledge of the pre-existing computer instructions.
E. A total knowledge of the users present and or future needs.
F. A complete understanding of the pre-existing instructions.
G. Knowing the users purpose or reasons for the interception.
H. That all the pre-existing instructions be executed.
I. All and or any of the user hooks be executed.
J. The result of the pre-existing instructions change.
K. Guidance or expertise from original authors or inventors.
L. Any additional physical, electronic or mechanical device.

NOTE : The procedure chosen to intercept is only used as an example and
can and could be changed to or combined with any EXTERNAL procedure
CALL from a program unit.

The computer language chosen to demonstrate this example is only
used as an example and can and could be changed to or combined with
another computer language.

The computer system chosen to demonstrate this example on is only
used as an example and can and could be changed to or combined with
another computer system or a number of combinations of computer
systems.

The intercept method used to demonstrate this example is only
used as one example of the method and can and could be changed in
order to comply with other computer systems operating systems.
```

Page 2 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

Below are the Tandem Guardian C30.06 Operating System calls that MAY be called by this program.

```

46. 000000 0 0 1
47. 000000 0 0 1
48. 000000 0 0 1
49. 000000 0 0 1
50. 000000 0 0 1
51. 000000 0 0 1
52. 000000 0 0 1
53. 000000 0 0 1
54. 000000 0 0 1
55. 000000 0 0 1
56. 000000 0 0 1
57. 000000 0 0 1
58. 000000 0 0 1
59. 000000 0 0 1
60. 000000 0 0 1
61. 000000 0 0 1
62. 000000 0 0 1
63. 000000 0 0 1
64. 000000 0 0 1
65. 000000 0 0 1
66. 000000 0 0 1
67. 000000 0 0 1
68. 000000 0 0 1
69. 000000 0 0 1
70. 000000 0 0 1
71. 000000 0 0 1
72. 000000 0 0 1
73. 000000 0 0 1
74. 000000 0 0 1
75. 000000 0 0 1
76. 000000 0 0 1
77. 000000 0 0 1
78. 000000 0 0 1
79. 000000 0 0 1
80. 000000 0 0 1
81. 000000 0 0 1
82. 000000 0 0 1
83. 000000 0 0 1
84. 000000 0 0 1
85. 000000 0 0 1
86. 000000 0 0 1
87. 000000 0 0 1
88. 000000 0 0 1
89. 000000 0 0 1
90. 000000 0 0 1
91. 000000 0 0 1
92. 000000 0 0 1
93. 000000 0 0 1
94. 000000 0 0 1
95. 000000 0 0 1
96. 000000 0 0 1
97. 000000 0 0 1
98. 000000 0 0 1
99. 000000 0 0 1
100. 000000 0 0 1
101. 000000 0 0 1
102. 000000 0 0 1
103. 000000 0 0 1
104. 000000 0 0 1
105. 000000 0 0 1
106. 000000 0 0 1
107. 000000 0 0 1
108. 000000 0 0 1
109. 000000 0 0 1
110. 000000 0 0 1
111. 000000 0 0 1
112. 000000 0 0 1
113. 000000 0 0 1
114. 000000 0 0 1
115. 000000 0 0 1
116. 000000 0 0 1
117. 000000 0 0 1
118. 000000 0 0 1
119. 000000 0 0 1
120. 000000 0 0 1
121. 000000 0 0 1
122. 000000 0 0 1
123. 000000 0 0 1
124. 000000 0 0 1
125. 000000 0 0 1
126. 000000 0 0 1
127. 000000 0 0 1
128. 000000 0 0 1
129. 000000 0 0 1
130. 000000 0 0 1
131. 000000 0 0 1
132. 000000 0 0 1
133. 000000 0 0 1
134. 000000 0 0 1
135. 000000 0 0 1
136. 000000 0 0 1
137. 000000 0 0 1
138. 000000 0 0 1
139. 000000 0 0 1
140. 000000 0 0 1
141. 000000 0 0 1
142. 000000 0 0 1
143. 000000 0 0 1
144. 000000 0 0 1
145. 000000 0 0 1
146. 000000 0 0 1
147. 000000 0 0 1
148. 000000 0 0 1
149. 000000 0 0 1
150. 000000 0 0 1
151. 000000 0 0 1
152. 000000 0 0 1
153. 000000 0 0 1
154. 000000 0 0 1
155. 000000 0 0 1
156. 000000 0 0 1
157. 000000 0 0 1
158. 000000 0 0 1
159. 000000 0 0 1
160. 000000 0 0 1
161. 000000 0 0 1
162. 000000 0 0 1
163. 000000 0 0 1
164. 000000 0 0 1
165. 000000 0 0 1
166. 000000 0 0 1
167. 000000 0 0 1
168. 000000 0 0 1
169. 000000 0 0 1
170. 000000 0 0 1
171. 000000 0 0 1
172. 000000 0 0 1
173. 000000 0 0 1
174. 000000 0 0 1
175. 000000 0 0 1
176. 000000 0 0 1
177. 000000 0 0 1
178. 000000 0 0 1
179. 000000 0 0 1
180. 000000 0 0 1
181. 000000 0 0 1
182. 000000 0 0 1
183. 000000 0 0 1
184. 000000 0 0 1
185. 000000 0 0 1
186. 000000 0 0 1
187. 000000 0 0 1
188. 000000 0 0 1
189. 000000 0 0 1
190. 000000 0 0 1
191. 000000 0 0 1
192. 000000 0 0 1
193. 000000 0 0 1
194. 000000 0 0 1
195. 000000 0 0 1
196. 000000 0 0 1
197. 000000 0 0 1
198. 000000 0 0 1
199. 000000 0 0 1
200. 000000 0 0 1
201. 000000 0 0 1
202. 000000 0 0 1
203. 000000 0 0 1
204. 000000 0 0 1
205. 000000 0 0 1
206. 000000 0 0 1
207. 000000 0 0 1
208. 000000 0 0 1
209. 000000 0 0 1
210. 000000 0 0 1
211. 000000 0 0 1
212. 000000 0 0 1
213. 000000 0 0 1
214. 000000 0 0 1
215. 000000 0 0 1
216. 000000 0 0 1
217. 000000 0 0 1
218. 000000 0 0 1
219. 000000 0 0 1
220. 000000 0 0 1
221. 000000 0 0 1
222. 000000 0 0 1
223. 000000 0 0 1
224. 000000 0 0 1
225. 000000 0 0 1
226. 000000 0 0 1
227. 000000 0 0 1
228. 000000 0 0 1
229. 000000 0 0 1
230. 000000 0 0 1
231. 000000 0 0 1
232. 000000 0 0 1
233. 000000 0 0 1
234. 000000 0 0 1
235. 000000 0 0 1
236. 000000 0 0 1
237. 000000 0 0 1
238. 000000 0 0 1
239. 000000 0 0 1
240. 000000 0 0 1
241. 000000 0 0 1
242. 000000 0 0 1
243. 000000 0 0 1
244. 000000 0 0 1
245. 000000 0 0 1
246. 000000 0 0 1
247. 000000 0 0 1
248. 000000 0 0 1
249. 000000 0 0 1
250. 000000 0 0 1
251. 000000 0 0 1
252. 000000 0 0 1
253. 000000 0 0 1
254. 000000 0 0 1
255. 000000 0 0 1
256. 000000 0 0 1
257. 000000 0 0 1
258. 000000 0 0 1
259. 000000 0 0 1
260. 000000 0 0 1
261. 000000 0 0 1
262. 000000 0 0 1
263. 000000 0 0 1
264. 000000 0 0 1
265. 000000 0 0 1
266. 000000 0 0 1
267. 000000 0 0 1
268. 000000 0 0 1
269. 000000 0 0 1
270. 000000 0 0 1
271. 00
```

Page 3 (2) \$SYSTEM.SYSTEM.EXTDECSU Copyright 1992, by Overlord Inc.

4150. 000000 1 0 EXTERNAL;
 4151. 000000 0 0
 4631. 000000 0 0 ?SECTION PROGRAMFILENAME
 4632. 000000 0 0 PROC PROGRAMFILENAME (NAME) CALLABLE;
 4633. 000000 1 0 !OUT
 4634. 000000 1 0 !FILE NAME
 4635. 000000 1 0 EXTERNAL;

NAME	Variable	INT	Indirect	L-003
4636. 000000 0 0				
4838. 000000 0 0				
4839. 000000 0 0				
4840. 000000 1 0				
4841. 000000 1 0				
4842. 000000 1 0				
4843. 000000 1 0				
4844. 000000 1 0				

RECEIVECHT	Variable	INT	Direct	L-004
SENDCHT	Variable	INT	Direct	L-003
4845. 000000 0 0				
5971. 000000 0 0				
5972. 000000 0 0				
5973. 000000 1 0				
5974. 000000 1 0				
5975. 000000 1 0				

LEN	Variable	INT	Direct	L-003
NAME	Variable	STRING	Indirect	L-004
5976. 000000 0 0				
Source file: (1)				
61. 000000 0 0				
62. 000000 0 0				
63. 000000 0 0				
Source file: (3)				
187. 000000 0 0				
188. 000000 0 0				
189. 000000 1 0				
190. 000000 1 0				
191. 000000 1 0				
192. 000000 1 0				
193. 000000 1 0				
194. 000000 1 0				
195. 000000 1 0				
196. 000000 1 0				

BUF	Variable	INT	EXT Pointer	L-012
CPU	Variable	INT	Direct	L-013
LEN	Variable	INT	Direct	L-010
PIN	Variable	INT	Indirect	L-006
SYSTEM	Variable	INT	Direct	L-005
TIME	Variable	FIXED (0)	Indirect	L-007
227. 000000 0 0				

Page 4 [3] \$SYSTEM."GUARD.PCPUCTL

Copyright 1992, by Overlord Inc.

```

228. 000000 0 0 INT PROC GETPEEKCONFIGURATION( CPU, BUF, LEN, TIME, PIN, SYSTEM )
229. 000000 1 0 CPU,
230. 000000 1 0 INT EXT BUF,
231. 000000 1 0 EXT BUF,
232. 000000 1 0 LEN,
233. 000000 1 0 FIXED .TIME;
234. 000000 1 0 INT .PIN;
235. 000000 1 0 INT SYSTEM;
236. 000000 1 0 EXTERNAL;

BUF Variable INT EXT Pointer L-012
CPU Variable INT Direct L-013
LEN Variable INT Direct L-010
PIN Variable INT Indirect L-006
SYSTEM Variable INT Direct L-005
TIME Variable FIXED (0) Indirect L-007

Source file: [1] $SYSTEM.SAVE.EXAMPLE 1992-12-04 12:13:07
64. 000000 0 0

```

Page 5 (1) \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

66. 000000 0 0
67. 000000 0 0
68. 000000 0 0
69. 000000 0 0
70. 000000 0 0
71. 000000 0 0
72. 000000 0 0
73. 000000 0 0
74. 000000 0 0
75. 000000 0 0
76. 000000 0 0
77. 000000 0 0
78. 000000 0 0
79. 000000 0 0
80. 000000 0 0
81. 000000 0 0
82. 000000 0 0
83. 000000 0 0
84. 000000 0 0
85. 000000 0 0
86. 000000 0 0
87. 000000 0 0
88. 000000 0 0
89. 000000 0 0
90. 000000 0 0
91. 000000 1 0
92. 000000 1 0

TOSVERSION^PROCEDURE^ADDRESS Variable INT Direct L-003

93. 000000 0 0
94. 000000 0 0
95. 000000 1 0
96. 000000 1 0

GUARDIAN^VERSION^LEVEL Variable INT Direct L-003

97. 000000 0 0

```

Below are the pre and post EXTERNAL user hook definitions for the Tandem Guardian TOSVERSION intercept procedures.

NOTE : The names chosen for the pre and post user hooks are only used as an example and these procedures can and could be named other names.

The parameters chosen to be passed to the pre and post user hooks are used only for example and the number of parameters and or names can and could be changed, deleted, and or added to.

In this example the pre user hook procedure "before^TOSVERSION^CALL" is called from the intercept TOSVERSION procedure passing the Tandem Guardian procedure TOSVERSION address.

In this example the post user hook procedure "after^TOSVERSION^CALL" is called from the intercept TOSVERSION procedure passing the Tandem Guardian version level received from the Tandem Guardian procedure TOSVERSION.

```

PROC before^TOSVERSION^CALL( TOSVERSION^procedure^address );
  INT TOSVERSION^procedure^address;
  EXTERNAL;

PROC after^TOSVERSION^CALL( Guardian^version^level );
  INT Guardian^version^level;
  EXTERNAL;

```

Page 6 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
99. 000000 0 0
100. 000000 0 0
101. 000000 0 0
102. 000000 0 0
103. 000000 0 0
104. 000000 0 0
105. 000000 0 0
106. 000000 0 0
107. 000000 0 0
108. 000000 0 0
109. 000000 0 0
110. 000000 0 0
111. 000000 0 0
112. 000000 0 0
113. 000000 0 0
114. 000000 0 0
115. 000000 0 0
116. 000000 0 0
117. 000000 0 0
118. 000000 0 0
119. 000000 0 0
120. 000000 0 0
121. 000000 0 0
122. 000000 0 0
123. 000000 0 0
124. 000000 0 0
125. 000000 0 0
126. 000000 0 0

.....
TOSVERSION: This is normally a Tandem Guardian operating system CALL that
program unit(s) would CALL to see what operating system the program unit(s)
are running on. Then the program unit(s) can determine if the version is a
proper version of the operating system, and proper action can be taken if
needed.
!
Since this program unit does not have a MAIN procedure it can be used as a
User and or System library program unit.
When program unit(s) use this program unit as a library, this program unit
will intercept the TOSVERSION CALL to the Tandem Guardian operating system
and user hooks CAN be utilized to modify and or enhance the original
program unit(s).
Since many program units may CALL this particular procedure as part of
their initialization process, it is a good candidate to intercept, so that
the original program unit(s) can be enhanced and or modified.
In This example, TOSVERSION will be intercepted in order to allow user
hooks to be placed prior to the real TOSVERSION Tandem Guardian CALL as
well as after in order to modify or enhance the pre-existing program
unit(s).
.....
```

SUBSTITUTE SHEET (RULE 26)

```

129. 000000 0 0 ;
129. 000000 0 0 ;INT PROC TOSVERSION;
130. 000000 1 0 ;
131. 000000 1 0 ;
131. 000000 1 0 ; BEGIN
132. 000000 1 1 ;
133. 000000 1 1 ; INT
134. 000000 1 1 ; .Copyright(0:15)
135. 000031 1 1 ; .Author(0:8)
136. 000050 1 1 ; .overlord^version(0:14)
137. 000050 1 1 ;
138. 000050 1 1 ; INT
139. 000050 1 1 ;
140. 000050 1 1 ;
141. 000050 1 1 ;
142. 000050 1 1 ;
143. 000050 1 1 ; INT
144. 000050 1 1 ;
145. 000050 1 1 ; INT
146. 000050 1 1 ;
147. 000050 1 1 ;

```

Copyright 1992, by Overlord Inc.

```
149. 000050 1 1
150. 000050 1 1
151. 000050 1 1
152. 000050 1 1
153. 000050 1 1
154. 000050 1 1
155. 000050 1 1
156. 000050 1 1
157. 000050 1 1
158. 000050 1 1
159. 000050 1 1
160. 000050 1 1
161. 000050 1 1
162. 000050 1 1
163. 000050 1 1
164. 000050 1 1
165. 000050 1 1
166. 000050 1 1
167. 000050 1 1
168. 000050 1 1
169. 000050 1 1
170. 000050 1 1
171. 000050 1 1
172. 000050 1 1
173. 000050 1 1
174. 000050 1 1
175. 000050 1 1
176. 000050 1 1
177. 000050 1 1
178. 000050 1 1
179. 000050 1 1
180. 000050 1 1
181. 000050 1 1
182. 000050 1 1
183. 000050 1 1
184. 000050 1 1
185. 000050 1 1
186. 000050 1 1

.....
NOTE: Using this program unit as a library program unit :
System Library;

If this program unit is going to be used as a System Library
program unit then the Tandem Guardian TOSVERSION procedure name
should be changed to another name using the BIND utility on the
pre-existing System Library.

The "TOSVERSION" name variable should be changed to the new name,
also the "TOSVERSION" name length variable should be changed to the
length in BYTES of the new name.

This program unit should then be compiled and BOUND with the proper
pre-existing System Library program unit prior to the OSIMAGE
being built.

WARNING : Do not CALL ABEND, DEBUG or STOP in any user hooks if
this program unit will be used as a System Library
program unit.

With pre-existing User Library;

This program unit should be compiled and BOUND with the
pre-existing User Library program unit and a new User library
program unit should be created and linked to the proper program
unit(s).

User Library;

This program unit should be compiled and then linked with the
proper program unit(s).
.....
```


Page 9 (1) \$SYSTEM.DAVE EXAMPLE

Copyright 1992, by Overlord Inc.

188.	000050	1	1
189.	000050	1	1
190.	000050	1	1
191.	000050	1	1
192.	000050	1	1
193.	000050	1	1
194.	000050	1	1
195.	000050	1	1
196.	000050	1	1
197.	000050	1	1
198.	000050	1	1
199.	000050	1	1

NOTE: Using this program unit as part of a MAIN program unit:
This program unit can be combined with a pre-existing MAIN program
unit by doing the following :

A. BIND this program unit into a pre-existing MAIN program unit.

Page 10 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
201. 000050 1 1 1
202. 000050 1 1 1
203. 000055 1 1 1
204. 000055 1 1 1
205. 000055 1 1 1
206. 000055 1 1 1
207. 000055 1 1 1
208. 000127 1 1 1
209. 000134 1 1 1

INT .TOSVERSION^name{0:4} := {"TOSVERSION"},
    TOSVERSION^name^length := 10;

STRING .s^TOSVERSION^name := @TOSVERSION^name '<<' 1;

TOSVERSION^address := SYSTEMENTRYPOINTLABEL( s^TOSVERSION^name,
    TOSVERSION^name^length );
```

Page 11 (1) \$SYSTEM.SAVE.EXAMPLE

[illegible]

Page 12 (1) \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

224. 000142 1 1
225. 000142 1 1
226. 000142 1 1
227. 000142 1 1
228. 000142 1 1
229. 000142 1 1
230. 000142 1 1
231. 000142 1 1
232. 000142 1 1
233. 000142 1 1
234. 000142 1 1
235. 000142 1 1
236. 000142 1 1
237. 000142 1 1
238. 000142 1 1

```

NOTE : It is possible that the before^TOSVERSION^CALL procedure could execute a RETURN statement with it's own values which would return control to the originating program unit(s) and not execute the remaining instructions in this procedure.

This could be of value to the user if some program unit(s) must be told that they are on operating system versions that they are not really on and do not require the real operating system version to be checked.

Page 13 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
240. 000142 1 1 ; .....  
241. 000142 1 1 ; .....  
242. 000142 1 1 ; .....  
243. 000142 1 1 ; .....  
244. 000142 1 1 ; CALL the Tandem Guardian TOSVERSION procedure and get the Tandem Guardian  
245. 000142 1 1 ; operating system release level.  
246. 000142 1 1 ; .....  
247. 000142 1 1 ; .....  
248. 000142 1 1 ; .....  
249. 000142 1 1 ; .....  
250. 000142 1 1 ; .....  
251. 000143 1 1 ; .....  
252. 000144 1 1 ; .....  
253. 000145 1 1 ; .....  
      STACK TOSVERSION^address;  
      CODE( DPCL ); ^level;  
      STORE version^level;
```

SUBSTITUTE SHEET (RULE 26)

Page 14 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
255. 000145 1 1
256. 000145 1 1
257. 000145 1 1
258. 000145 1 1
259. 000145 1 1
260. 000145 1 1
261. 000145 1 1
262. 000145 1 1
263. 000145 1 1
264. 000145 1 1
265. 000150 1 1
266. 000153 1 1

.....]
.....]
.....]
Check to see if the post^user hook is present and if so then CALL the
after^TOSVERSION^CALL prior to returning the value of the Tandem Guardian
Operating system level to the originating program unit(s).
.....]
.....]
.....]
IF post^user^hook^present > 0 THEN
CALL after^TOSVERSION^CALL( version^level );
```

Page 15 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
268. 000153 1 1 .....
269. 000153 1 1 .....
270. 000153 1 1 .....
271. 000153 1 1 .....
272. 000153 1 1 .....
273. 000153 1 1 .....
274. 000153 1 1 .....
275. 000153 1 1 .....
276. 000153 1 1 .....
277. 000153 1 1 .....
278. 000153 1 1 .....
279. 000153 1 1 .....
280. 000153 1 1 .....
281. 000153 1 1 .....
282. 000153 1 1 .....

NOTE : It is possible that the after^TOSVERSION^CALL procedure could
execute a RETURN statement with it's own values which would return
control to the originating program unit(s) and not execute the
remaining instructions in this procedure.

This could be of value to the user if some program unit(s) must
be told that they are on a operating system version that they are
not really on, but do require that the real operating system version
first be checked.
```

Copyright 1992, by Overlord Inc.

```
284. 000153 1 1
285. 000153 1 1
286. 000153 1 1
287. 000153 1 1
288. 000153 1 1
289. 000153 1 1
290. 000153 1 1
291. 000153 1 1
292. 000153 1 1
293. 000153 1 1
294. 000155 1 1
295. 000155 1 1
```

```
.....
RETURN the value from the Tandem Guardian TOSVERSION procedure which will
return control back to the original program unit that made the CALL to the
Tandem Guardian TOSVERSION procedure.
.....
```

RETURN version^level;

END;

AUTHOR
COPYRIGHT

Variable	INT	Indirect	L+002
Variable	INT	Indirect	L+001
Variable	INT	Direct	L+004
Variable	INT	Direct	G+000
Variable	INT	Direct	L+000
Variable	INT	Indirect	L+003
Variable	INT	Direct	L+006
Variable	INT	Direct	L+005
Variable	INT	Direct	S-000
Variable	STRING	Indirect	L+013
Variable	INT	Direct	L+010
Variable	INT	Indirect	L+011
Variable	INT	Direct	L+012
Variable	INT	Direct	L+007

000000	041557	070171	071151	063550	072040	041171	020117	073145	000010	071154	067562	062040	044556	061456	026040	030471	034462
000020	042157	067141	066144	020112	027040	045545	067156	062544	000030	074440	043471	030103	031460	027060	033056	030060	027117
000040	046122	042103	031460	027060	033056	040461	030056	030060	000050	052117	051526	042522	051511	047516	070414	070434	070445
000060	100000	024733	010401	000000	020376	000454	024700	010401	000070	000000	020376	000454	000002	070464	100012	024744	170411
000100	030001	024700	002055	170401	000025	003673	100020	026047	000110	170402	000025	003706	100011	026047	170403	000025	003712
000120	100017	026047	170411	000025	003724	100005	026047	170413	000130	040412	024711	027000	044410	040405	001000	016003	040410
000140	024700	027000	040410	000032	044407	040406	001000	016003	000150	040407	024700	027000	040407	125003			

296. 000000 0 0

Page 17 (1) \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
298. 000000 0 0
299. 000000 0 0
300. 000000 0 0
301. 000000 0 0
302. 000000 0 0
303. 000000 0 0
304. 000000 0 0
305. 000000 0 0
306. 000000 0 0
307. 000000 0 0
308. 000000 0 0
309. 000000 0 0
310. 000000 0 0
311. 000000 0 0
312. 000000 0 0
313. 000000 0 0
314. 000000 0 0
315. 000000 0 0
316. 000000 0 0
317. 000000 0 0
318. 000000 0 0
319. 000000 0 0
320. 000000 0 0
321. 000000 0 0
322. 000000 0 0
323. 000000 0 0
324. 000000 1 0
325. 000000 1 0
326. 000000 1 0
327. 000000 1 0
328. 000000 1 0
329. 000000 1 0
330. 000000 1 0
331. 000000 1 0
332. 000000 1 0
333. 000000 1 0
334. 000000 1 0
335. 000000 1 0
336. 000000 1 0
337. 000000 1 0
338. 000000 1 0
339. 000000 1 0
340. 000000 1 1

before^TOSVERSION^CALL : This procedure ( IF PRESENT ) can intercept the
pre-existing CALL to TOSVERSION prior to the CALL being placed. Several
uses can be made of this user hook. The following list is just a sample
of one or more possible ways this user hook could be used:

A. Do not call the real TOSVERSION, instead RETURN a value from here.
B. Add additional computer instructions prior to the TOSVERSION CALL.
C. Log a message that the pre-existing instructions CALL TOSVERSION.
D. Log a message of the time pre-existing instructions CALL TOSVERSION.
E. Count the number of times that TOSVERSION is CALLED.
F. Calculate the time between CALLS to TOSVERSION.
G. Gain access to pre-existing data values in the program unit(s).
H. Change pre-existing data values in the program unit(s).

The user can change the scope of the original program unit(s) by using this
hook without one or more of the requirements listed earlier. This allows
the user to have additional options and control on the modification and or
enhancements of the pre-existing computer instructions without the need
of the original authors and or inventors guidance or expertise.

PROC before^TOSVERSION^CALL( TOSVERSION^procedure^address );
INT TOSVERSION^procedure^address;

NOTE : This procedure can be removed from this program unit if needed.
If left empty, as it is, it will still be called but no additional
logic will be executed.

User computer instructions can be placed in this area that
should be executed prior the the REAL TOSVERSION procedure CALL
being made if needed.

BEGIN
END;
```

TOSVERSION^PROCEDURE^ADDRESS Variable INT Direct L-003

000000 125004

341. 000000 0 0

Page 18 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```
343. 000000 0 0
344. 000000 0 0
345. 000000 0 0
346. 000000 0 0
347. 000000 0 0
348. 000000 0 0
349. 000000 0 0
350. 000000 0 0
351. 000000 0 0
352. 000000 0 0
353. 000000 0 0
354. 000000 0 0
355. 000000 0 0
356. 000000 0 0
357. 000000 0 0
358. 000000 0 0
359. 000000 0 0
360. 000000 0 0
361. 000000 0 0
362. 000000 0 0
363. 000000 0 0
364. 000000 0 0
365. 000000 0 0
366. 000000 0 0
367. 000000 0 0
368. 000000 1 0
369. 000000 1 0
370. 000000 1 0

.....
after^TOSVERSION^CALL : This procedure ( IF PRESENT ) can intercept the
pre-existing CALL to TOSVERSION after the CALL was placed. Several
users can be made of this user hook. The following list is just a sample
of one or more possible ways this user hook could be used:

A. Do not RETURN the value from TOSVERSION, instead RETURN another value.
B. Add additional computer instructions after the TOSVERSION CALL.
C. Log a message that the pre-existing instructions CALL TOSVERSION.
D. Log a message of the times pre-existing instructions CALL TOSVERSION.
E. Count the times that TOSVERSION is CALLED.
F. Calculate the time it took to call TOSVERSION.
G. Gain access to pre-existing data values in the program unit(s).
H. Change pre-existing data values in the program unit(s).

The user can change the scope of the original program unit by using this
hook without one or more of the requirements listed earlier. This allows
the user to have additional options and control on the modification and or
enhancements of the pre-existing computer instructions without the need
of the original authors and or inventors, guidance and or expertise.
.....
PRCC after^TOSVERSION^CALL( Guardian^version^level );
IF^ Guardian^version^level;
```

Page 19 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

372.	000000	1	0	
373.	000000	1	0	
374.	000000	1	0	
375.	000000	1	0	
376.	000000	1	0	
377.	000000	1	0	
378.	000000	1	0	
379.	000000	1	0	
380.	000000	1	0	
381.	000000	1	0	
382.	000000	1	0	
383.	000000	1	0	
384.	000000	1	0	
385.	000000	1	0	

NOTE : This procedure can be removed from this program unit if needed.
If left empty, it will still be called, but no additional logic will be executed.
User computer instructions can be placed in this area that should be executed after the REAL TOSVERSION procedure CALL is made, if needed.

Copyright 1992, by Overlord Inc.

```

387. 000000 1 0
388. 000000 1 0
389. 000000 1 0
390. 000000 1 0
391. 000000 1 0
392. 000000 1 0
393. 000000 1 0
394. 000000 1 0
395. 000000 1 0
396. 000000 1 0
397. 000000 1 0
398. 000000 1 0
399. 000000 1 0
400. 000000 1 0
401. 000000 1 0
402. 000000 1 0
403. 000000 1 0
404. 000000 1 0
405. 000000 1 0
406. 000000 1 0
407. 000000 1 0
408. 000000 1 0
409. 000000 1 0
410. 000000 1 0
411. 000000 1 0
412. 000000 1 0
413. 000000 1 0
414. 000000 1 0
415. 000000 1 0
416. 000000 1 0
417. 000000 1 0
418. 000000 1 0
419. 000000 1 0

```

.....

The following example is one of may uses that this user hook could be used for.

EXAMPLE : This hook will allow pre-existing program unit(s) using this program unit as a library and making a CALL to TOSVERSION from the original program unit(s), to also CALL the RESERVELCBS Procedure, before returning control back to the original program unit(s).

Some of the pre-existing program units may CALL the Tandem Guardian Procedure RESERVELCBS later, in this case the later CALL will override this CALL to RESERVELCBS and may require that the RESERVELCBS be intercepted and similar user hook logic be placed in the user hook "before"RESERVELCBS"CALL".

NOTE : The RESERVELCBS intercept procedure as well as the before"RESERVELCBS"CALL and after"RESERVELCBS"CALL are not included in this example but the intercept CONCEPT would be the same, and could also be incorporated in this program unit.

Other pre-existing program unit(s) may not currently CALL the RESERVELCBS procedure. This user hook will allow these original pre-existing program unit(s) to be modified and enhanced to CALL the RESERVELCBS procedure if the proper system resources are available and these pre-existing program unit(s) make a CALL to the Tandem Guardian TOSVERSION procedure.

.....

Page 21 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

421. 000000 1 0
422. 000000 1 0 BEGIN
423. 000000 1 1
424. 000000 1 1 .Copyright{0:15] := ["Copyright 1992, By Overlord Inc."],
425. 000020 1 1 .Author{0:8] := ["Donald J. Kennedy"],
426. 000031 1 1 .overlord^version{0:14] := ["G90C30.06.00.OLRDC30.06.A10.00"];
427. 000050 1 1
428. 000050 1 1 STRUCT cpu^config^values( * );
429. 000050 1 1 BEGIN
430. 000050 1 1 processor^type;
431. 000050 1 2 total^pcbs;
432. 000050 1 2 memory^size;
433. 000050 1 2 syspool^size;
434. 000050 1 2 mappool^size;
435. 000050 1 2 total^lcbs;
436. 000050 1 2 total^tles;
437. 000050 1 2 total^bpts;
438. 000050 1 2 END;
439. 000050 1 1
440. 000050 1 1 STRUCT cpu^current^values( * );
441. 000050 1 1 BEGIN
442. 000050 1 1 delta^time^cpu^idle;
443. 000050 1 2 items^on^ready^list;
444. 000050 1 2 delta^time^ready^queued;
445. 000050 1 2 page^fault^count;
446. 000050 1 2 items^queued^for^memory;
447. 000050 1 2 delta^time^memory^queued;
448. 000050 1 2 dispatch^count;
449. 000050 1 2 delta^time^send^busy;
450. 000050 1 2 cache^hit^count;
451. 000050 1 2 disc^io^count;
452. 000050 1 2 pcb^free^count;
453. 000050 1 2 memory^locked;
454. 000050 1 2 current^syspool;
455. 000050 1 2 current^mappool;
456. 000050 1 2 current^lcbs;
457. 000050 1 2 current^tles;
458. 000050 1 2 current^bpts;
459. 000050 1 2 END;
460. 000050 1 1

```

Page 22 (1) \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

462. 000050 1 1
463. 000050 1 1
464. 000050 1 1
465. 000050 1 1
466. 000050 1 1
467. 000050 1 1
468. 000050 1 1
469. 000050 1 1
470. 000050 1 1
471. 000050 1 1
472. 000050 1 1
473. 000050 1 1
474. 000050 1 1
475. 000050 1 1
476. 000050 1 1
477. 000050 1 1
478. 000050 1 1
479. 000050 1 1
480. 000050 1 1
481. 000050 1 1
482. 000050 1 1
483. 000050 1 1
484. 000064 1 1

      .cpu^config^buffer {0:( $LEN( cpu^config^values ) - 1 ) / 2 },
      .cpu^current^buffer{0:( $LEN( cpu^current^values ) - 1 ) / 2 },
      .cpu^config ( cpu^config^values ) = cpu^config^buffer,
      .cpu^current( cpu^current^values ) = cpu^current^buffer,
      .current^program^file^name;

      .EXT x^cpu^config^buffer
      .EXT x^cpu^current^buffer

      .EXT x^system^number
      .EXT x^pin
      .EXT x^pid
      .current^percent^lcbs^free
      .allocate^send^lcbs
      .allocate^receive^lcbs
      .program^loop^counter
      .cpu^config^length
      .cpu^current^length
      .my^program^file^name(0:11)

      := $XADR( cpu^config^buffer ),
      := $XADR( cpu^current^buffer );

      := 0,
      := 0,
      := 0,
      := 0,
      := 0,
      := 0,
      := 0,
      := $LEN( cpu^config^values ),
      := $LEN( cpu^current^values ),
      := ( 12 * [ " " ] );

```

Page 23 [1] \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

486. 000064 1 1
487. 000064 1 1
488. 000064 1 1
489. 000064 1 1
490. 000064 1 1
491. 000064 1 1
492. 000064 1 1
493. 000064 1 1
494. 000064 1 1
495. 000064 1 1
496. 000064 1 1
497. 000064 1 1
498. 000064 1 1
499. 000064 1 1
500. 000064 1 1
501. 000064 1 1
502. 000064 1 1
503. 000064 1 1
504. 000064 1 1
505. 000064 1 1
506. 000064 1 1
507. 000064 1 1
508. 000064 1 1
509. 000064 1 1
510. 000064 1 1
511. 000064 1 1
512. 000064 1 1
513. 000064 1 1
514. 000064 1 1
515. 000072 1 1
516. 000100 1 1
517. 000106 1 1
518. 000114 1 1
519. 000122 1 1
520. 000130 1 1
521. 000136 1 1
522. 000144 1 1
523. 000152 1 1
524. 000160 1 1
525. 000166 1 1
526. 000174 1 1
527. 000202 1 1
528. 000210 1 1
529. 000216 1 1
530. 000216 1 1
531. 000216 1 1
532. 000216 1 1
533. 000320 1 1
534. 000323 1 1
535. 000330 1 1
536. 000332 1 1

```

The threshold and table settings are located here

NOTE : To add more programs change "max^programs" to increase the size of the program^file^name^table and add program names and set the SEND and RECEIVE LCB values to the proper values for each program in the "program^file^name^table". Leave unused entries as 'UNUSED' so the empty table space will not be checked.

```

INT lcb^saftey^threshold := 40; ! At least 40% of the LCB's must be free
! in order to RESERVE the LCB's in the
! table. IF not, no LCB's will be reserved
! even if the file name is found.

LITERAL max^programs = 15; ! Maximum programs that the table can hold
entry^length = 6; ! Size of each table entry
table^size = max^programs * entry^length;

INT program^file^name^table[0:table^size - 1] :=

```

Program File Name	Reserve SEND LCB's	Reserve RECEIVE LCB's	Program Entry Number
"BINSERV"	2	2	1
"COROL"	2	2	2
"COMINT"	1	1	3
"EDIT"	1	2	4
"ENFORM"	3	3	5
"FUP"	2	2	6
"INSPECT"	1	1	7
"OLORDCPU"	1	1	8
"OLORDSYS"	1	1	9
"OLORDMON"	1	1	10
"PERUSE"	1	2	11
"SYMSERV"	2	2	12
"TACL"	1	1	13
"TAL"	2	2	14
"UNUSED"	1	1	15

```

FIXED my^time := 0F;

my^pid := MYPID;
my^pin := my^pid.<8:15>;
my^cpu.<8:15> := my^pid.<0:7>;
my^system^number := MYSYSTEMNUMBER;

```

Page 24 [1] \$SYSTEM.SAVE.EXAMPLE

```

538. .....[.....]
539. .....[.....]
540. .....[.....]
541. .....[.....]
542. .....[.....]
543. .....[.....]
544. .....[.....]
545. .....[.....]
546. .....[.....]
547. .....[.....]
548. .....[.....]
549. .....[.....]
550. .....[.....]
551. .....[.....]
552. .....[.....]
553. .....[.....]
554. .....[.....]
555. .....[.....]
556. .....[.....]
557. .....[.....]
558. .....[.....]

Get current system status to see what percent of LCB's are free

CALL GETPEEKCONFIGURATION( my^cpu, x^cpu^config^buffer,
                           cpu^config^length,
                           my^time, my^pin,
                           my^system^number );

CALL GETPEEKSTATISTICS( my^cpu, x^cpu^current^buffer,
                        cpu^current^length,
                        my^time, my^pin,
                        my^system^number );

```


Page 25 (1) \$SYSTEM.SAVE.EXAMPLE

Copyright 1992, by Overlord Inc.

```

560. current^percent^lcb^free
561. := $INTR($DBL(cpu^current^lcb^free) * 1000
562. / $DBL(cpu^config^total^lcb));
563.
564. @current^program^file^name := @program^file^name^table;
565.
566. IF lcb^saftey^threshold < current^percent^lcb^free THEN
567. BEGIN
568. CALL PROGRAMFILENAME( my^program^file^name );
569. FOR program^loop^counter := 0 TO ( max^programs - 1 ) DO
570. BEGIN
571. IF current^program^file^name = my^program^file^name(8) FOR 4 THEN
572. BEGIN
573. allocate^send^lcb := current^program^file^name(4);
574. allocate^receive^lcb := current^program^file^name(5);
575. CALL RESERVELCBS( allocate^send^lcb, allocate^receive^lcb );
576. END;
577. @current^program^file^name := @current^program^file^name '+' entry^length;
578. IF current^program^file^name = "UNUSED" THEN
579. program^loop^counter := ( max^programs - 1 );
580. END;
581.
582. END;
583.
584. END;
585.
586.
587.
588.
589.
590.
591.
592.
593.
594.
595.
596.
597.
598.
599.
600.
601.
602.
603.
604.
605.
606.
607.
608.
609.
610.
611.
612.
613.
614.
615.
616.
617.
618.
619.
620.
621.
622.
623.
624.
625.
626.
627.
628.
629.
630.
631.
632.
633.
634.
635.
636.
637.
638.
639.
640.
641.
642.
643.
644.
645.
646.
647.
648.
649.
650.
651.
652.
653.
654.
655.
656.
657.
658.
659.
660.
661.
662.
663.
664.
665.
666.
667.
668.
669.
670.
671.
672.
673.
674.
675.
676.
677.
678.
679.
680.
681.
682.
683.
684.
685.
686.
687.
688.
689.
690.
691.
692.
693.
694.
695.
696.
697.
698.
699.
700.
701.
702.
703.
704.
705.
706.
707.
708.
709.
710.
711.
712.
713.
714.
715.
716.
717.
718.
719.
720.
721.
722.
723.
724.
725.
726.
727.
728.
729.
730.
731.
732.
733.
734.
735.
736.
737.
738.
739.
740.
741.
742.
743.
744.
745.
746.
747.
748.
749.
750.
751.
752.
753.
754.
755.
756.
757.
758.
759.
760.
761.
762.
763.
764.
765.
766.
767.
768.
769.
770.
771.
772.
773.
774.
775.
776.
777.
778.
779.
780.
781.
782.
783.
784.
785.
786.
787.
788.
789.
790.
791.
792.
793.
794.
795.
796.
797.
798.
799.
800.
801.
802.
803.
804.
805.
806.
807.
808.
809.
810.
811.
812.
813.
814.
815.
816.
817.
818.
819.
820.
821.
822.
823.
824.
825.
826.
827.
828.
829.
830.
831.
832.
833.
834.
835.
836.
837.
838.
839.
840.
841.
842.
843.
844.
845.
846.
847.
848.
849.
850.
851.
852.
853.
854.
855.
856.
857.
858.
859.
860.
861.
862.
863.
864.
865.
866.
867.
868.
869.
870.
871.
872.
873.
874.
875.
876.
877.
878.
879.
880.
881.
882.
883.
884.
885.
886.
887.
888.
889.
890.
891.
892.
893.
894.
895.
896.
897.
898.
899.
900.
901.
902.
903.
904.
905.
906.
907.
908.
909.
910.
911.
912.
913.
914.
915.
916.
917.
918.
919.
920.
921.
922.
923.
924.
925.
926.
927.
928.
929.
930.
931.
932.
933.
934.
935.
936.
937.
938.
939.
940.
941.
942.
943.
944.
945.
946.
947.
948.
949.
950.
951.
952.
953.
954.
955.
956.
957.
958.
959.
960.
961.
962.
963.
964.
965.
966.
967.
968.
969.
970.
971.
972.
973.
974.
975.
976.
977.
978.
979.
980.
981.
982.
983.
984.
985.
986.
987.
988.
989.
990.
991.
992.
993.
994.
995.
996.
997.
998.
999.
1000.

```

Copyright 1992, by Overlord Inc.

1	PCB^FREE^COUNT	64,2	INT	Direct													
1	MEMORY^LOCKED	66,2	INT	Direct													
1	CURRENT^SYSPPOOL	70,2	INT	Direct													
1	CURRENT^MAPPOOL	72,2	INT	Direct													
1	CURRENT^LCBS	74,2	INT	Direct													
1	CURRENT^TLES	76,2	INT	Direct													
1	CURRENT^BPTS	100,2	INT	Direct													
	CURRENT^PERCENT^LCBS^FREE	Variable	INT	Direct	L+017												
	CURRENT^PROGRAM^FILE^NAME	Variable	INT	Indirect	L+006												
	ENTRY^LENGTH	Literal	INT	\$000006													
	GUARDIAN^VERSION^LEVEL	Variable	INT	Direct	L-003												
	LCB^SAFETY^THRESHOLD	Variable	INT	Direct	L+026												
	MAX^PROGRAMS	Literal	INT	\$000017													
	MY^CPU	Variable	INT	Direct	L+013												
	MY^PID	Variable	INT	Direct	L+016												
	MY^PIN	Variable	INT	Direct	L+015												
	MY^PROGRAM^FILE^NAME	Variable	INT	Indirect	L+025												
	MY^SYSTEM^NUMBER	Variable	INT	Direct	L+014												
	MY^TIME	Variable	INT	Direct	L+161												
	OVERLORD^VERSION	Variable	FIXED (0)	Indirect	L+003												
	PROGRAM^FILE^NAME^TABLE	Variable	INT	Direct	L+027												
	PROGRAM^LOOP^COUNTER	Variable	INT	Direct	L+022												
	TABLE^SIZE	Literal	INT	\$000132													
	X^CPU^CONFIG^BUFFER	Variable	EXT Pointer	L+007													
	X^CPU^CURRENT^BUFFER	Variable	EXT Pointer	L+011													
000000	041557	070171	071151	063550	072040	030471	034462	026040	000010	041171	020117	073145	071154	067562	062040	044556	061456
000020	042157	067141	066144	020112	027040	045545	067156	062544	000030	074440	043471	030103	031460	027060	033056	030060	027117
000040	046122	042103	031460	027060	033056	040461	030056	030060	000050	020040	020040	020040	020040	020040	020040	020040	020040
000060	020040	020040	020040	020040	041111	047123	042522	053040	000070	000002	020040	041517	041117	046040	020040	000002	020040
000100	041517	046511	047124	020040	000001	000001	042504	044524	000110	020040	020040	000001	000002	042516	043117	051115	020040
000120	000003	000003	043125	050040	020040	020040	000002	000002	000130	044516	051520	042501	052040	000001	000001	047514	047522
000140	042103	050125	000001	000001	047514	047522	042123	054523	000150	000001	000001	047514	047522	042115	047516	000001	000001
000160	050105	051125	051505	020040	000001	000002	051531	046523	000170	042522	053040	000002	000002	052101	041514	020040	020040
000200	000001	000001	052101	016040	020040	020040	000002	000002	000210	025125	047125	051505	042052	000001	000001	070565	024700
000220	070740	003204	024700	070740	003214	024700	070740	003232	000230	024700	070740	003241	024700	002001	100000	170404	130001
000240	024711	100000	170405	130001	000002	000002	024755	000002	000250	000002	100020	100102	024755	070740	003262	100050	024711
000260	002132	000002	000002	024733	002135	170401	000025	003511	000270	100020	026047	170402	000025	003551	100132	026047	170403
000300	000025	003530	100017	026047	170425	100377	070413	100014	000310	026047	070427	000035	003551	100132	026047	027000	044416
000320	040416	006377	044415	040416	030110	100377	070413	060411	000330	027000	040414	040413	060407	040423	070561	070415	044416
000340	005376	024777	100771	024700	027000	000107	040413	060411	000350	040424	070561	070413	060407	040423	070561	070415	044416
000360	027000	000107	103036	143405	000327	100000	100144	000222	000370	102005	142404	070561	070413	060407	040423	070561	070415
000400	040426	040417	000215	013047	170425	024700	027000	100000	000410	010437	170406	103010	173425	100004	026207	015012	103004
000420	143406	044420	103005	143406	044421	040420	040421	024711	000430	027000	170406	103010	173425	100004	026207	015012	103004
000440	000200	100004	024717	015002	100016	044422	040422	104001	000450	034422	001016	016336	125004	025125	047125	051505	042052

Page 27 (1) \$SYSTEM.SAVE.EXAMPLE

ABEND	PROC
AFTER^TOSVERSION^CALL	PROC
BEFORE^TOSVERSION^CALL	PROC
DEBUG	PROC
GETPEEKCONFIGURATION	PROC
GETPEEKSTATISTICS	PROC
MYPID	PROC
MYSYSTEMNUMBER	PROC
PROGRAMFILENAME	PROC
RESERVELCBS	PROC
SYSTEMENTRYPOINTLABEL	PROC
TOSVERSION	PROC

GLOBAL MAP

External	INT
1000216	INT
1000000	INT
External	INT
External	INT
External	INT
External	INT
External	INT
External	INT
External	INT
External	INT
1000055	INT

SUBSTITUTE SHEET (RULE 26)

Page 28 [1] \$SYSTEM.SAVE.EXAMPLE

ENTRY POINT MAP BY NAME FOR FILE: \CLXA.\$WORK.COE.cpatent2

LOAD MAPS

SP	PEP	BASE	LIMIT	ENTRY	ATTRS	NAME	DATE	TIME	LANGUAGE	SOURCE	FILE
00	004	000163	000642	000401		AFTER^TOSVERSION^CALL	04DEC92	12:28	TAL	\$SYSTEM.SAVE.EXAMPLE	
00	003	000162	000162	000162		BEFORE^TOSVERSION^CALL	04DEC92	12:28	TAL	\$SYSTEM.SAVE.EXAMPLE	
00	002	000005	000161	000062		TOSVERSION	04DEC92	12:28	TAL	\$SYSTEM.SAVE.EXAMPLE	

SUBSTITUTE SHEET (RULE 26)

WHAT IS CLAIMED IS:

1. An apparatus for translating one or more steps of a pre-existing method for carrying out a predetermined function, wherein user defined steps can
5 be incorporated therein, comprising:

circuitry for detecting a step from the pre-existing method which is a candidate for a translation; and

10 circuitry for determining if a previously defined, user supplied, pre-translation set of steps is to be executed before executing any predetermined translation steps, and in response to the determining steps, executing the set of pre-translation steps where indicated.

15

2. An apparatus according to claim 1 further including means for determining if a previously defined, user supplied, post-translation set of steps is to be
20 executed after executing any predetermined translation steps, and in response thereto, executing the post steps where indicated.

3. A process of translating one or more steps of a pre-existing method for carrying out a
25 predetermined function, wherein user defined steps can be incorporated therein, in accordance with the apparatus of claim 1, comprising:

detecting a step from the pre-existing method which is a candidate for a translation; and

30 determining if a previously defined, user supplied, pre-translation set of steps is to be executed before executing any predetermined translation steps, and in response to the determining step, executing the set of pre-translation steps where indicated.

35

4. The process of claim 3 further including the step of:

5 determining if a previously defined, user supplied, post-translation set of steps is to be executed after executing any predetermined translation steps, and in response thereto, executing the post steps where indicated.

10 5. A method of executing a predefined set of steps, including altering one or more of the steps in a predetermined fashion wherein user defined steps can be incorporated therein, in accordance with the apparatus of claim 1, comprising:

15 detecting a step which is a candidate for alteration;

executing the altering steps; and
determining if a previously defined, user supplied, post-alteration set of steps is to be executed after executing the set of post-alteration steps where indicated.

20

6. The method of claim 5 further including, after the detecting step, the step of:

25 determining if a previously defined, user supplied, pre-alteration set of steps is to be executed before executing any predetermined altering steps, and in response to the determining step, executing the set of pre-alteration steps where indicated.

30 7. A method of intercepting and modifying pre-existing instructions at run time in a computer program being executed in an apparatus as in claim 1, comprising:

35 intercepting a selected instruction and determining if it is a candidate for modification;

subsequent to the modifying step, evaluating
if a previously defined, operator supplied, post-
modification set of steps exists;

5 executing the operator supplied, post-
modification set of steps as indicated; and

 returning to the sequence of steps immediately
after the detected step, thereby continuing the process.

determining if an alterable, previously -
defined, pre-modification set of instructions is to be
executed, and in response thereto, executing the pre-
modification set of instructions, if any; and

5 modifying or executing the intercepted
instruction.

8. The method of claim 7 further including
the step of:

10 determining if an alterable, previously
defined, post-modification set of instructions is to be
executed, and in response thereto, executing the post-
modification set of instructions, if any.

15 9. A method of allocating resources within a
multiple node, multiple processor system, wherein at
least some of the nodes are spaced apart and are
interconnected by communication links, wherein one or
more of the processors includes an apparatus as in claim
20 1, the method comprising:

 carrying out a sequence of steps in a
predetermined process in a selected processor at one of
the nodes;

25 detecting a step in the sequence which is to
be carried out and which is a candidate for run-time
modification;

 intercepting the detected step and evaluating
if a previously defined, operator supplied, pre-
modification set of steps exists;

30 interrupting the sequence and executing the
operator supplied pre-modification set of steps as
indicated;

 modifying the candidate step using a
predetermined sequence of one or more predetermined
35 modifier steps;